



Product Data Sheet

DB952IAS

950 Series Integrated Base Sounder with Isolator

General

The DB952IAS is a range of integrated, self monitoring base sounders with integral short-circuit isolator for use on Series 950 and Series 990 systems. They incorporate a base into which a series 950 or 990 detector, or beacon can be fitted. It may also be used with a red (AS952CAP-R) or white (AS952CAP-W) cap for stand-alone use.

Tones

The DB952IAS sounders support multiple tones. A low tone range is useful in areas such as hospitals where a fire alert is initially intended to warn staff only. The sounder may be set to the high range for general use.

In addition to the standard tones in the DB952IAS, a slow whoop tone to Dutch standard NEN2575 is available in the DB952IAS-NEN, as well as a German standard DIN tone version in the DB952IAS-DIN.

Synchronisation

Synchronisation of tones ensures the integrity of the signal—tones from different sounders do not merge into one signal that could be mistaken for a different tone. DB952IAS sounders are synchronised with each other in both 'alert' and 'evacuate' modes.

Self Test

The acoustic self-test means that the sounder listens to itself when it is switched on. If no sound is detected a fault signal is transmitted when the sounder is polled.

The same self-test feature may also be used during commissioning or periodical maintenance testing. The sounder may simply be activated for at least 5 seconds and the control panel checked for a fault signal. If none is received, the sounder is working properly.



Standard Features

- Two tone ranges 55 to 75 dB and 75 to 91 dB
- Synchronisation of 'alert' and 'evacuate' tones
- Individual sounder addressing
- Available with built-in isolator
- Acoustic self-test
- Slow whoop option available

DB952IAS

950 Series Integrated Base Sounder with Isolator

Specifications

Operating voltages	
Power supply	17 - 28 VDC
Protocol pulses	5 - 9 V
Current consumption at 24 V	
Switch-on surge, <1s	1.2 mA
Quiescent	< 1.2 mA
Sounder operated 50 - 75 dB	5 mA
Sounder operated 75 - 91dB	5 mA
Sound output	
Maximum at 90°	91db(A)
Maximum to EN54	83dB(A)
Sound pressure level	Tone dependent
Environmental	
Operating temperature	-20°C to +60°C
Humidity (no condensation)	0 - 95%
IP rating	21D

Ordering Information

Part No.	Description
DB952IAS	950 Series Integrated Base Sounder with Isolator
AS952CAP-R	Red Cap for DB952AS Series Sounder Bases
AS952CAP-W	White Cap for DB952AS Series Sounder Bases

